



## PRODUCT DATA

### LUBRIKO M6

Lubriko M6 is a general purpose grease for ball and roller bearings in electric motors, pillow blocks and for plain bearings. This popular grease has stood the test of time and remains one of the most widely used general purpose greases in our line. It has excellent shear stability and will pick up approximately 20% of its overall weight in water and remain a workable lubricant.

#### TYPICAL PROPERTIES

NLGI Grade .....	2
Thickener Type .....	Sodium/Calcium
Texture .....	Smooth-Tacky
Color .....	Brown
Work Penetration, ASTM D 217	
77°F, 60 Strokes .....	265-295
Dropping Point, °F, ASTM D 2265, min .....	365
Timken E.P. Test, ASTM D 2509	
OK Load, Lbs. ....	65
Base Fluid Properties, ASTM D 445	
Viscosity @ 100°C, cSt.....	127-157
Flash Point, °F, min .....	500
Pour Point, °F .....	+25

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.